



PIPE DIA. SIZE IN [mm]	WALL THICKNESS W. T.	OUTSIDE DIAMETER O. D.	A	B	C	O. D. B.	APPROX. WEIGHT IBS/FT	WATERWAY AREA SQ. FT.
12" [300]	2.90" C	17.80"	3.81"	3.94"	6"	19.67"	146	.785
15" [375]	3.125" C	21.25"	3.81"	3.94"	6"	22.66"	194	1.23
18" [450]	3.375" C	24.75"	3.81"	3.94"	6"	25.66"	240	1.77

GENERAL NOTES:

1. PIPE IS MANUFACTURED IN ACCORDANCE WITH APPLICABLE SPECIFICATIONS WITH REINFORCING STEEL AS REQUIRED BY ASTM C-76 (LATEST REVISION): "STANDARD SPECIFICATION FOR REINFORCED CONCRETE CULVERT, STORM DRAIN, AND SEWER PIPE". GASKET JOINTS ARE IN ACCORDANCE WITH AASHTO M-170 (LATEST REVISION) OR ASTM C-443 (LATEST REVISION): "STANDARD SPECIFICATION FOR JOINTS FOR CIRCULAR CONCRETE SEWER AND CONCRETE PIPE, USING RUBBER GASKETS".

★
SHERMANDIXIE
 NASHVILLE, TN-KNOXVILLE, TN- ELIZABETHTOWN, KY-DAYTON, OH
 FRANKLIN, TN-CHATTANOOGA, TN- LEXINGTON, KY-CULLMAN, AL

**GASKETED REINFORCED CONCRETE PIPE
 STORM SEWER 12" - 18" DIAMETER**

SCALE: NTS

PH* 1-800-737-0707

DWG. NO. PI-L10

DATE:05/05/05

SHEET* 1 OF 1