



PIPE DIAMETER SIZE IN [mm]	WALL THICKNESS INCHES	OUTSIDE DIAMETER INCHES	A INCHES	B INCHES	APPROX. WEIGHT LBS/FT	WATERWAY AREA SQ. FT.
24" [650]	3.88 [C]	31.76	3.8	3.94	366	3.14
30" [750]	4.38 [C]	38.77	4.6	4.72	476	4.91
36" [900]	4.89 [C]	45.78	4.6	4.72	654	7.07
42" [1050]	5.39 [C]	52.78	5	5.12	843	9.62
48" [1200]	5.15 [B]	58.3	5	5.12	890	12.57
54" [1350]	5.64 [B]	65.3	5	5.12	1100	15.90
60" [1500]	6.14 [B]	72.3	5	5.12	1320	19.64

GENERAL NOTES:

1. PIPE IS MANUFACTURED IN ACCORDANCE WITH APPLICABLE SPECIFICATIONS WITH REINFORCING STEEL AS REQUIRED BY ASTM C-76 (LATEST REVISION): "STANDARD SPECIFICATION FOR REINFORCED CONCRETE CULVERT, STORM DRAIN, AND SEWER PIPE". GASKET JOINTS ARE IN ACCORDANCE WITH AASHTO M-170 (LATEST REVISION) OR ASTM C-443 (LATEST REVISION): "STANDARD SPECIFICATION FOR JOINTS FOR CIRCULAR CONCRETE SEWER AND CONCRETE PIPE, USING RUBBER GASKETS".

 SHERMANDIXIE <small>NASHVILLE, TN-KNOXVILLE, TN- ELIZABETHTOWN, KY-DAYTON, OH FRANKLIN, TN-CHATTANOOGA, TN- LEXINGTON, KY-CULLMAN, AL</small>	
PH* 1-800-737-0707	DWG. NO. PI-L11
DATE:05/05/05	SHEET* 1 OF 1

**GASKETED REINFORCED CONCRETE PIPE
STORM SEWER 24" – 60" DIAMETER**

SCALE: NTS